

# ValueJet

ValueJet VJ-1624W



## Professional Dye Sublimation Printer

The compact ValueJet 1624W (1625 mm – 64”) is ideally suited for your daily sublimation needs. The printer will deliver speeds ranging from 9 to 38 m<sup>2</sup>/h. The machine is fit for both startup and established businesses wanting to extend their product portfolio.

You don't need to be an expert to run the VJ-1624W printer, as it is very easy to operate and maintain. Competitively priced, ValueJet 1624W will deliver constant quality for volume production runs as well as short print runs.

The VJ-1624W model features a latest generation variable drop 8 channel print head featuring 8 rows of 180 nozzles, allowing output resolutions between 360 x 720 dpi and 1440 x 1440 dpi.

### Product Highlights

- Transfer sublimation printing up to 1625 mm (63.97”)
- Latest generation 1440 nozzle piezo head
- Typical production speeds between 14 & 27.5 m<sup>2</sup>/h
- Mutoh water-based disperse dye inks
- Ideal for production of soft signage, sportswear, gadgets, ...
- Environmentally friendly printing - high level of operator safety

### Application Possibilities

Explore new revenue opportunities such as high quality in-store textile decoration and displays, textile banners, pop-ups, sportswear, personalised home decoration, gadgets, shirts and many more.



# MUTOH

Mutoh Belgium nv - T: +32 59 56 14 00 / E: [mutoh@mutoh.be](mailto:mutoh@mutoh.be) / W: [www.mutoh.eu](http://www.mutoh.eu)



ValueJet VJ-1624W



## Dye Sublimation Printer

## SPECIFICATIONS

### Technical Key Specifications

Print Technology	Drop-on-demand Micro Piezo Inkjet Technology
Print Head	1
Nozzle Configuration	180 nozzles x 8 lines - 360 nozzles per colour
Drop Mass Range (pl)	3.3 to 34.1
Head Heights (mm)	Low : 1.5 / Middle: 2.5 / High : 4.0

### Media Specifications

Max. Media Width	1625 mm (63,97")
Max. Print Width	1615 mm (63,58")
Max. Media Thickness	0.3 / 1.3 / 2.8 mm *

\* : Max. media thickness is specified per head height

Media Measurements *	Ø 150 mm / 2" & 3" / 30 kg
----------------------	----------------------------

\* : Standard non-motorised roll-off system

### Ink Specifications

Ink Type	Disperse Dye Sublimation
Ink Volume	1000 ml
Ink Colours	CMYK
Ink Consumption	15 ml / m <sup>2</sup>
UV durability	3 to 6 months outdoor

### Performance

High Quality (540 x 720)	9.0 m <sup>2</sup> /h
Quality (720 x 720)	14.0 m <sup>2</sup> /h
Production (360 x 720)	20.5 m <sup>2</sup> /h
Speed Production (360 x 360)	27.5 m <sup>2</sup> /h
Billboard (360 x 360)	38.0 m <sup>2</sup> /h

### Power Consumption

During Printing	210 W
In Stand-by	38 W
Power Supply	AC 100-120 V / AC 200-240 - 60/50 Hz

### Recommended Working Environment

Temperature	20 °C - 30 °C with Δt: max. 2 °C/h
Humidity	40 % - 60 % (no condensation) with ΔRH: max. 5 % RH/h

### Machine Measurements

Width x Depth x Height	2698 x 885 x 1261 mm
Weight	160 kg

Distributed by:

